Zhuhai RaySharp Technology Co., Ltd.

NO.100 Technology Rd.6, High-tech Zone Zhuhai,Guangdong,P.R.CHINA, 519085

4CH 1080P W ireless Kit

Unit Price($)	**4ch wireless NVR with 4PK Wireless Cameras Kit (not including HDD)**

NVR			**Camera**	
Model	**RS-H1104NR-N-W**		**Model**	**RS-CH2BSCC-W-30W**
Picture			**Picture**	
Description			**Video**	
Video	Inputs	4CH IMP.	Imaging Device	2MP CMOS (1/2.7"); SC2235H
Live	Resolution	1, 1920x1,080 Full HD	Effective Pixels	1, 920(H)x1, 080(V)
	Frame rate	- Main stream: Max. 15fps@1080p per channel - Sub stream: Max 15fps @960*540 per channel	Scanning System	Progressive
	Resolution	1080p	Sync Mode	Internal
	Multi Screen display	1 / 4 / TEED	Mechanical Resolution	1080P
Performance			Min. Illumination	Color:1W:0.1Lux;
Operating System	Embedded	Linux	Camera output	RJ45
	Installation wizard	Support	**Lens**	
Recording	Compression	H. 264/Protocol Raysharp)	Focus Region	Around 4.1mm
	Recording bandwidth	Up to 8Mbps (Each Stream Maximum), Max 2Mbps per channel)	Max. Aperture Ratio	F2.1
	Record Rate	Main stream: Max. 15fps@1080p per channel	Angular Field of View	Diagonal : 101°
	Mode	Manual, Schedule (Continuous/Event), Event (Pre/Post)	**Optical Mode**	
	Event	Video Loss, Motion (Sensitivity Level 1~8)	Weather Mode	Auto
	Overwrite Modes	Off / 1H / Auto (1H/2H/3H/4H/5H/6H/7H)	Lens Control	None
	Pre-alarm	Min. 1sec	White Balance	Auto
	Post-alarm	Up to 5min (30sec, 1/2/5min)	Wide Dynamic Range	D-WDR
	Local Schedule	Continuous, Event, Motion	Contrast Enhancement	None
Seach & Playback	Playback function	Fast forward / fast bward (2x, 4x, 8x, 16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x) Step Forward	Digital Noise Reduction	2DNR
Network	Live stream	60fps@1080p, 60fps@960*540	OSD	N/A
	Protocol support	TCP/IP, UDP/IP, RTP/UDP, RTP/TCP, RTSP, NTP, HTTP, DHCP, SMTP, DNS, DDNS, UPNP	Flip&Mirro	Manual (OSH/OSV/Both optional)
	Monitoring	Web, Mobile, Native viaFor PC Mac	Day & Night	Mode:D/N, Auto
Remote Monitoring	Web/App viewer	Supported OS - PC : Windows® 7 , Windows® 8, Windows® 10 Mac OS X® 10.10 or above - Mobile : Android Ver6.0 or above IOS7. 0 or above Supported Browser - Microsoft Internet Explorer (Ver. 11, 10, 9, 8), Mozilla Firefox Ver 16 x or higher, Google Chrome Ver 44. x or lower Safari® 10 or above	Night Distance	65ft/20M (Total darkness)
	Protocol support	TCP/IP, UDP/IP, UDP, P2P	Video output	Web
Storage	Internal HDD	1 SATA HDD: Max 6TB	Transmission distance	Wireless 40m
		2 USB Ports	**Environmental**	
	Alert format (alarm out)	H. 264, AVI, MP4	Operating Temperature/ Humidity	-10°C ~ 60°C / less than 85% RH ⊞ Startup: -10 °C ~ 60°C
Interface			Lightning Protection	6KV
Monitors	VGA	1 VGA (1, 024x768, 1, 280x1, 024, 1, 280x 720, 1, 440x900)	**Electrical**	
	HDMI	1 HDMI (1, 024x768, 1, 280x1, 024, 1, 280x 720, 1, 440x900)	Input Voltage	12V/500mA DC Adapter
	Simultaneous Output	VGA and HDMI		
Audio	Inputs/Output	N/A		
	Compression	N/A		
Alarm	Alert	N/A		
PTZ control	RS-485	N/A		
Connections	Ethernet	1 RJ45 10/100 Base-T		
	USB	USB 2.0, 2 ports (Front/Rear)		
	Application Support	Mouse, Remote control		
General				
Electrical	Input Voltage/Current	12V/2A DC Adaptor		
Environmental	Operating Temperature/Humidity	0°C~+40°C (32°F ~ 104°F) / 20% ~ 85%RH		